

Nominal Diameter

2,7 = 5 mm²



TEESING

WE MAKE YOUR TECHNOLOGY WORK

Rectus Series

20



Mini industrial coupling with internationally used profile. Frequent use in medical technology and chemistry/pharmacy. Coupling system with single-hand operation. High flow despite small dimensions plus many applications with a variety of media.

Series 20 with additional end connections available on request.

Working Temperature*

-15°C up to +200°C (FKM) depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.

Other designs in series 20

The following other designs can be found from page:

► Brass / Steel P. 18



Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

35 bar

Features

- Low pressure drop

Material

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Technical Description

Connecting Force 0 bar: 25 N
Connecting Force 6 bar: 35 N

Connecting Force 0 bar: 25 N
Connecting Force 6 bar: 35 N

Vacuum Coupling: 96%
Vacuum connected: 96%


Vacuum Coupling: 96%
Vacuum Plug: 96%
Vacuum connected: 96%

Interchangeability (KA only)


- Walther 06-003

Flow diagrams


Air




Air



Water








Water





Couplings – with valve

Series 20KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	9		26	5		10			AISI 303	20KAAM05RVX
	M 5	9		26	5		10			AISI 316 L	20KAAM05EVX
	G 1/8	11		28	7		10			AISI 303	20KAAW10RVX
	G 1/8	11		28	7		10			AISI 316 L	20KAAW10EVX
 <p>Female Thread</p>	G 1/8	12		28	7		10			AISI 303	20KAIW10RVX
	G 1/8	12		28	7		10			AISI 316 L	20KAIW10EVX
 <p>Hose Barb</p>	4 mm			35	13		10			AISI 316 L	20KATF04EVX
 <p>with Plastic Hose Connection</p>	3 x 4 mm	9		34	7	5	10		M 7 x 0,5	AISI 316 L	20KAKO04EVX
	3 x 5 mm	9		34	7	5	10		M 7 x 0,5	AISI 316 L	20KAKO05EVX
	4 x 6 mm	9		34	7	5	10		M 8 x 0,5	AISI 303	20KAKO06RVX
	4 x 6 mm	9		34	7	5	10		M 8 x 0,5	AISI 316 L	20KAKO06EVX
 <p>Panel Mount with Plastic Hose Connection</p>	3 x 4 mm	12	11	45	7	17	10	3	M 7 x 0,5	AISI 303	20KAKS04RVX
	3 x 5 mm	12	11	45	7	17	10	3	M 7 x 0,5	AISI 303	20KAKS05RVX
	4 x 6 mm	12	11	45	7	17	10	3	M 8 x 0,5	AISI 303	20KAKS06RVX

TEESING





WE MAKE YOUR TECHNOLOGY WORK

Please consider our security advices on the pages 12/13








Plugs – without valve

Series 20KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	7		18	5					AISI 303	20SFAM05RXX
	M 5	7		18	5					AISI 316 L	20SFAM05EXX
	G 1/8	11		20	7					AISI 303	20SFAW10RXX
	G 1/8	11		20	7					AISI 316 L	20SFAW10EXX
 <p>Female Thread</p>	G 1/8	12		19	7					AISI 303	20SFIW10RXX
	G 1/8	12		19	7					AISI 316 L	20SFIW10EXX
 <p>Hose Barb</p>	4 mm			24	13		7			AISI 303	20SFTF04RXX
	4 mm			24	13		7			AISI 316 L	20SFTF04EXX
	5 mm			22	13		9			AISI 303	20SFTF05RXX
 <p>with Plastic Hose Connection</p>	3 x 4 mm	8		25	7	5			M 7 x 0,5	AISI 316 L	20SFKO04EXX
	3 x 5 mm	8		25	7	5			M 7 x 0,5	AISI 316 L	20SFKO05EXX
	4 x 6 mm	8		25	7	5			M 8 x 0,5	AISI 303	20SFKO06RXX
	4 x 6 mm	8		25	7	5			M 8 x 0,5	AISI 316 L	20SFKO06EXX








	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	9		26	5		10			AISI 303	20KBAM05RVX
	M 5	9		26	5		10			AISI 316 L	20KBAM05EVX
	G 1/8	11		28	7		10			AISI 303	20KBAW10RVX
	G 1/8	11		28	7		10			AISI 316 L	20KBAW10EVX
 <p>Female Thread</p>	G 1/8	12		28	7		10			AISI 303	20KBIW10RVX
	G 1/8	12		28	7		10			AISI 316 L	20KBIW10EVX
 <p>Hose Barb</p>	4 mm			35	13		10			AISI 316 L	20KBTf04EVX
 <p>with Plastic Hose Connection</p>	3 x 4 mm	9		34	7	5	10		M 7 x 0,5	AISI 316 L	20KBKO04EVX
	3 x 5 mm	9		34	7	5	10		M 7 x 0,5	AISI 316 L	20KBKO05EVX
	4 x 6 mm	9		34	7	5	10		M 8 x 0,5	AISI 303	20KBKO06RVX
	4 x 6 mm	9		34	7	5	10		M 8 x 0,5	AISI 316 L	20KBKO06EVX
 <p>Panel Mount with Plastic Hose Connection</p>	3 x 4 mm	12	11	45	7	17	10	3	M 7 x 0,5	AISI 303	20KBKS04RVX
	3 x 5 mm	12	11	45	7	17	10	3	M 7 x 0,5	AISI 303	20KBKS05RVX
	4 x 6 mm	12	12	45	7	17	10	3,5	M 8 x 0,5	AISI 303	20KBKS06RVX



Plugs – with valve

Series 20KB

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	M 5	9		28	5					AISI 303	20SBAM05RVX
	M 5	9		28	5					AISI 316 L	20SBAM05EVX
	G 1/8	11		30	7					AISI 303	20SBAW10RVX
	G 1/8	11		30	7					AISI 316 L	20SBAW10EVX
 <p>Female Thread</p>	G 1/8	12		30	7					AISI 303	20SBIW10RVX
	G 1/8	12		30	7					AISI 316 L	20SBIW10EVX
 <p>Hose Barb</p>	4 mm	8		37	13					AISI 316 L	20SBTF04EVX
 <p>with Plastic Hose Connection</p>	3 x 4 mm	9		36	7	5		M 7 x 0,5	AISI 316 L	20SBKO04EVX	
	3 x 5 mm	9		36	7	5		M 7 x 0,5	AISI 316 L	20SBKO05EVX	
	4 x 6 mm	9		36	7	5		M 8 x 0,5	AISI 303	20SBKO06RVX	
	4 x 6 mm	9		36	7	5		M 8 x 0,5	AISI 316 L	20SBKO06EVX	
 <p>Panel Mount with Plastic Hose Connection</p>	3 x 4 mm	12	11	47	7	17		3	M 7 x 0,5	AISI 303	20SBKS04RVX
	3 x 5 mm	12	11	47	7	17		3	M 7 x 0,5	AISI 303	20SBKS05RVX
	4 x 6 mm	12	12	47	7	17		3,5	M 8 x 0,5	AISI 303	20SBKS06RVX

Nominal Diameter

3 = 7 mm²

Rectus Series

303

Mini industrial coupling with plug profile according to ISO 6150 C. Popular profile in analytical and medical technology. Above average flow rate performance for liquid and gaseous media.

Series 303 with additional end connections available on request.

Working Temperature*

-15°C up to +200°C (FKM)
depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: AISI 316L

Plug: AISI 316L

Seals: FKM

Technical Description

Dead space volume: 0,35 ml

Connecting Force 0 bar: 30 N

Connecting Force 6 bar: 60 N



Vacuum Coupling: 96%

Vacuum Plug: 96%

Vacuum connected: 96%

Interchangeability (KA only)

- ISO 6150 C




Flow diagrams**Air****Water****TEESING**

WE MAKE YOUR TECHNOLOGY WORK



Couplings – with valve




Series 303KB

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14		43	7		18			AISI 316L	303KBAW10EVX
	G 1/4	17		45	9		18			AISI 316L	303KBAW13EVX
 <p>Female Thread</p>	G 1/8	14		43	9		18			AISI 316L	303KBIW10EVX
	G 1/4	17		45	9		18			AISI 316L	303KBIW13EVX
 <p>with Plastic Hose Connection</p>	4 x 6 mm	14	12	49	7	6	18		M 10 x 1	AISI 316L	303KBKO06EVX
	6 x 8 mm	14	14	49	7	6	18		M 12 x 1	AISI 316L	303KBKO08EVX



Plugs – with valve

Series 303KB

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14		48,5	7					AISI 316L	303SBAW10EVX
	G 1/4	17		50,5	9					AISI 316L	303SBAW13EVX
 <p>Female Thread</p>	G 1/8	14		48,5	9					AISI 316L	303SBIW10EVX
	G 1/4	17		50,5	9					AISI 316L	303SBIW13EVX
 <p>with Plastic Hose Connection</p>	4 x 6 mm	14	12	54,5	7	6			M 10 x 1	AISI 316L	303SBKO06EVX
	6 x 8 mm	14	14	54,5	7	6			M 12 x 1	AISI 316L	303SBKO08EVX

Nominal Diameter

5 = 20 mm²



Rectus Series

21

Low Pressure



Other designs in series 21

The following other designs can be found from page:

- Brass / Steel P. 26
- Thermoplastic P. 176
- Safety P. 210
- Coded Systems P. 234

Interchangeability (KA only)

- Camozzi
- EWO
- Kani

Mini industrial coupling with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous media. Coupling system with single-hand operation. Small dimensions and large band width in materials and valve variants.

Series 21 with additional end connections available on request.

Dust Protections  (P. 250) for Coupling Part.-No. SK16S

Working Temperature*
-15°C up to +200°C (FKM) depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.



Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

35 bar

8 bar

Features

- All variants interchangeable

- Minimal, almost imperceptible leakage when uncoupling
- No air locked into the system during the coupling process

Material

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Technical Description

Connecting Force 0 bar: 35 N
Connecting Force 6 bar: 60 N

Vacuum Coupling: 96%
Vacuum connected: 96%

Dead space volume: 0,6 ml

Connecting Force 0 bar: 40 N
Connecting Force 6 bar: 80 N






Vacuum Coupling: 96%
Vacuum Plug: 96%
Vacuum connected: 96%

Dead space volume: 0,0006 ml

Connecting Force 0 bar: 35 N
Connecting Force 6 bar: 60 N

Vacuum Coupling: 96%
Vacuum Plug: 96%
Vacuum connected: 96%

Flow diagrams



WE MAKE YOUR TECHNOLOGY WORK



Couplings – with valve

Series 21KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/8	14		36	7		16			AISI 303	21KAAW10RVX
	G 1/8	14		36	7		16			AISI 316 L	21KAAW10EVX
	G 1/4	17		38	9		16			AISI 303	21KAAW13RVX
	G 1/4	17		38	9		16			AISI 316 L	21KAAW13EVX
	G 3/8	19		38	9		16			AISI 303	21KAAW17RVX
	G 3/8	19		38	9		16			AISI 316 L	21KAAW17EVX
<p>Female Thread</p>	G 1/8	14		36	9		16			AISI 303	21KAIW10RVX
	G 1/8	14		36	9		16			AISI 316 L	21KAIW10EVX
	G 1/4	17		38	9		16			AISI 303	21KAIW13RVX
	G 1/4	17		38	9		16			AISI 316 L	21KAIW13EVX
<p>Hose Barb</p>	6 mm	14		46	17		16			AISI 303	21KATF06RVX
	6 mm	14		46	17		16			AISI 316 L	21KATF06EVX
	8 mm	14		46	17		16			AISI 303	21KATF08RVX
	9 mm	14		46	17		16			AISI 303	21KATF09RVX
	10 mm	14		46	17		16			AISI 316 L	21KATF10EVX
<p>with Plastic Hose Connection</p>	4 x 6 mm	14		42	7	6	16		M 10 x 1	AISI 303	21KAKO06RVX
	4 x 6 mm	14		42	7	6	16		M 10 x 1	AISI 316 L	21KAKO06EVX
	6 x 8 mm	14		42	7	6	16		M 12 x 1	AISI 303	21KAKO08RVX





Plugs – without valve





Series 21KA

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
<p>Male Thread</p>	G 1/8	14		25	7					AISI 303	21SFAW10RXX
	G 1/8	14		25	7					AISI 316 L	21SFAW10EXX
	G 1/4	17		28	9					AISI 303	21SFAW13RXX
	G 1/4	17		28	9					AISI 316 L	21SFAW13EXX
	G 3/8	19		28	9					AISI 303	21SFAW17RXX
<p>Female Thread</p>	G 1/8	14		25	8					AISI 303	21SFIW10RXX
	G 1/8	14		25	8					AISI 316 L	21SFIW10EXX
	G 1/4	17		25	9					AISI 303	21SFIW13RXX
	G 1/4	17		25	9					AISI 316 L	21SFIW13EXX
	G 3/8	19		26	9					AISI 303	21SFIW17RXX





Plugs – without valve **Series 21KA**

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Hose Barb</p>	6 mm			32	17		9			AISI 303	21SFTF06RXX
	6 mm			32	17		9			AISI 316 L	21SFTF06EXX
	8 mm			32	17		9			AISI 303	21SFTF08RXX
	8 mm			32	17		9			AISI 316 L	21SFTF08EXX
	10 mm			33	17		12			AISI 303	21SFTF10RXX
	10 mm			33	17		12			AISI 316 L	21SFTF10EXX
 <p>with Plastic Hose Connection</p>	4 x 6 mm	12	12	32	7	6			M 10 x 1	AISI 303	21SFKO06RXX
	4 x 6 mm	12	12	32	7	6			M 10 x 1	AISI 316 L	21SFKO06EXX
	6 x 8 mm	14	14	32	7	6			M 12 x 1	AISI 303	21SFKO08RXX
	6 x 8 mm	14	14	32	7	6			M 12 x 1	AISI 316 L	21SFKO08EXX

Couplings – with valve **Series 21KB**

	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14		36	7		16			AISI 303	21KBAW10RVX
	G 1/8	14		36	7		16			AISI 316 L	21KBAW10EVX
	G 1/4	17		38	9		16			AISI 303	21KBAW13RVX
	G 1/4	17		38	9		16			AISI 316 L	21KBAW13EVX
	G 3/8	19		38	9		16			AISI 303	21KBAW17RVX
	G 3/8	19		38	9		16			AISI 316 L	21KBAW17EVX
 <p>Female Thread</p>	G 1/8	14		36	9		16			AISI 303	21KBIW10RVX
	G 1/8	14		36	9		16			AISI 316 L	21KBIW10EVX
	G 1/4	17		38	7		16			AISI 303	21KBIW13RVX
	G 1/4	17		38	7		16			AISI 316 L	21KBIW13EVX
 <p>Hose Barb</p>	6 mm	14		46	17		16			AISI 303	21KBTF06RVX
	6 mm	14		46	17		16			AISI 316 L	21KBTF06EVX
	8 mm	14		46	17		16			AISI 303	21KBTF08RVX
	9 mm	14		46	17		16			AISI 303	21KBTF09RVX
	10 mm	14		46	17		16			AISI 316 L	21KBTF10EVX
	 <p>with Plastic Hose Connection</p>	4 x 6 mm	14		42	7	6	16		M 10 x 1	AISI 303
4 x 6 mm		14		42	7	6	16		M 10 x 1	AISI 316 L	21KBKO06EVX
6 x 8 mm		14		42	7	6	16		M 12 x 1	AISI 303	21KBKO08RVX







	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14		40	7					AISI 303	21SBAW10RVX
	G 1/8	14		40	7					AISI 316 L	21SBAW10EVX
	G 1/4	17		42	9					AISI 303	21SBAW13RVX
	G 1/4	17		42	9					AISI 316 L	21SBAW13EVX
	G 3/8	19		42	9					AISI 303	21SBAW17RVX
	G 3/8	19		42	9					AISI 316 L	21SBAW17EVX
 <p>Female Thread</p>	G 1/8	14		40	9					AISI 303	21SBIW10RVX
	G 1/8	14		40	9					AISI 316 L	21SBIW10EVX
	G 1/4	17		42	7					AISI 303	21SBIW13RVX
	G 1/4	17		42	7					AISI 316 L	21SBIW13EVX
 <p>Hose Barb</p>	6 mm	14		50	17					AISI 303	21SBTF06RVX
	6 mm	14		50	17					AISI 316 L	21SBTF06EVX
	8 mm	14		50	17					AISI 303	21SBTF08RVX
	9 mm	14		50	17					AISI 303	21SBTF09RVX
	10 mm	14		50	17					AISI 316 L	21SBTF10EVX
 <p>with Plastic Hose Connection</p>	4 x 6 mm	14		46	7	6			M 10 x 1	AISI 303	21SBKO06RVX
	4 x 6 mm	14		46	7	6			M 10 x 1	AISI 316 L	21SBKO06EVX
	6 x 8 mm	14		46	7	6			M 12 x 1	AISI 303	21SBKO08RVX







Couplings – flat sealing

Series 21KL


	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14		36	7		16			AISI 303	21KLAW10RVX
	G 1/8	14		36	7		16			AISI 316 L	21KLAW10EVX
	G 1/4	17		38	9		16			AISI 303	21KLAW13RVX
	G 1/4	17		38	9		16			AISI 316 L	21KLAW13EVX
	G 3/8	19		38	9		16			AISI 303	21KLAW17RVX
	G 3/8	19		38	9		16			AISI 316 L	21KLAW17EVX
 <p>Female Thread</p>	G 1/8	14		36	9		16			AISI 303	21KLIW10RVX
	G 1/8	14		36	9		16			AISI 316 L	21KLIW10EVX
	G 1/4	17		38	9		16			AISI 303	21KLIW13RVX
	G 1/4	17		38	9		16			AISI 316 L	21KLIW13EVX
 <p>Hose Barb</p>	6 mm	14		46	17		16			AISI 316 L	21KLTF06EVX
	8 mm	14		46	17		16			AISI 303	21KLTF08RVX
	8 mm	14		46	17		16			AISI 316 L	21KLTF08EVX
	10 mm	14		46	17		16			AISI 316 L	21KLTF10EVX
 <p>with Plastic Hose Connection</p>	4 x 6 mm	14		42	7	6	16		M 10 x 1	AISI 303	21KLKO06RVX
	4 x 6 mm	14		42	7	6	16		M 10 x 1	AISI 316 L	21KLKO06EVX
	6 x 8 mm	14		42	7	6	16		M 12 x 1	AISI 303	21KLKO08RVX
	6 x 8 mm	14		42	7	6	16		M 12 x 1	AISI 316 L	21KLKO08EVX



	Connection A	HEX mm	HEX1 mm	L mm	L1 mm	L2 mm	D mm	B mm	G mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14		40	7					AISI 303	21SLAW10RVX
	G 1/8	14		40	7					AISI 316 L	21SLAW10EVX
	G 1/4	17		42	9					AISI 303	21SLAW13RVX
	G 1/4	17		42	9					AISI 316 L	21SLAW13EVX
	G 3/8	19		42	9					AISI 303	21SLAW17RVX
	G 3/8	19		42	9					AISI 316 L	21SLAW17EVX
 <p>Female Thread</p>	G 1/8	14		40	9					AISI 303	21SLIW10RVX
	G 1/8	14		40	9					AISI 316 L	21SLIW10EVX
 <p>Hose Barb</p>	5 mm	14		50	17					AISI 316 L	21SLTF05EVX
	6 mm	14		50	17					AISI 303	21SLTF06RVX
	6 mm	14		50	17					AISI 316 L	21SLTF06EVX
	10 mm	14		50	17					AISI 303	21SLTF10RVX
	10 mm	14		50	17					AISI 316 L	21SLTF10EVX
 <p>with Plastic Hose Connection</p>	4 x 6 mm	14		46	7	6			M 10 x 1	AISI 303	21SLKO06RVX
	4 x 6 mm	14		46	7	6			M 10 x 1	AISI 316 L	21SLKO06EVX
	6 x 8 mm	14		46	7	6			M 12 x 1	AISI 303	21SLKO08RVX
	6 x 8 mm	14		46	7	6			M 12 x 1	AISI 316 L	21SLKO08EVX

Nominal Diameter

7,4 = 43 mm²



Tema Series

1300

Low Pressure



Other designs in series 1300

The following other designs can be found from page:

► Brass / Steel P. 64

Series 1300 is used mainly for applications in the area of compressed air and liquids. Optimally suited to use with liquid and aggressive media. The coupling series stands out for its compact design and corrosion resistance. Ultra High Flow valve for optimum flow and low pressure drop.

Series 1300 with additional end connections available on request.

Dust Protections  (P. 250)
for Coupling Part.-No. 1315-QC
for Plug Part.-No. 1325-QC

Working Temperature*
-25°C up to +200°C (FKM)
depending on the medium.

* For temperatures below -25°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.



Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

50 bar

Features

- Single-hand operation
- Two-hand operation

Material




Coupling: AISI 316
Plug: AISI 316
Seals: FKM

Coupling: AISI 316
Plug: AISI 316
Seals: FKM

Interchangeability (KA only)

- Tema Design

Flow diagrams



WE MAKE YOUR TECHNOLOGY WORK



Couplings – with valve

Series 1300KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
<p>Female Thread</p>	G 1/4	18	49	8,75	22	1300KAIW13EVX



Plugs – without valve

Series 1300KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
<p>Male Thread</p>	G 1/8	13	35	9		1300SFAW10EXX
<p>Female Thread</p>	G 1/4	16	36	10		1300SFIW13EXX



Couplings – with valve

Series 1300KB

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
<p>Female Thread</p>	G 1/4	18	49	8	22	1300KBIW13EVX







Plugs – with valve

Series 1300KB

	Connection A	HEX mm	L mm	L1 mm	D mm	Part Number
<p>Female Thread</p>	G 1/4	18	44	9		1300SBIW13EVX

Cross-Reference-List

Connection	Thread	Rectus Part Number old	Tema Part Number old	Part Number new	Page
 Couplings – with valve					
Female Thread	G 1/4		1300 RV	1300KAIW13EVX	147
 Plugs – without valve					
Male Thread	G 1/8		13110 R	1300SFAW10EXX	147
Female Thread	G 1/4		13410 R	1300SFIW13EXX	147
 Couplings – with valve					
Female Thread	G 1/4		1300 NRV	1300KBIW13EVX	147
 Plugs – with valve					
Female Thread	G 1/4		13410 RV	1300SBIW13EVX	147



Other designs in series 25

The following other designs can be found from page:

- Brass / Steel P. 70
- Safety P. 214
- Safety Self-Venting P. 230
- Coded Systems P. 236

Interchangeability (KA only)

- Rectus 26
- Cejn 320
- various German Products

Universal industrial coupling with standard European profile for use with gaseous, liquid and aggressive media.









Coupling system with single-hand operation. High Flow valve for optimum flow and low pressure drop. The series stands out for its robust design and long service life even with the harshest use. The collar design minimises damage to the valve body.

Series 25 with additional end connections available on request.

Dust Protections  (P. 250)
for Coupling Part.-No. SK23S
for Plug Part.-No. SK12S

Working Temperature*
-15°C up to +200°C (FKM)
depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.




		
<p>Working Pressure** 35 bar ** maximum static working pressure with design factor 4 to 1.</p>	<p>35 bar</p>	<p>8 bar</p>
<p>Features</p> <ul style="list-style-type: none"> • Minimal, almost imperceptible leakage when uncoupling • No air locked into the system during the coupling process 		
<p>Material Coupling: AISI 303 / AISI 316 L Plug: AISI 303 / AISI 316 L Seals: FKM</p>		
<p>Technical Description Connecting Force 0 bar: 40 N Connecting Force 6 bar: 120 N Vacuum Coupling: 96% Available on request with O-ring seal for vacuum when coupled.</p>	<p>Dead space volume: 1,5 ml Connecting Force 0 bar: 40 N Connecting Force 6 bar: 120 N Vacuum Coupling: 96% Vacuum Plug: 96% Available on request with O-ring seal for vacuum when coupled.</p>	<p>Dead space volume: 0,001 ml Connecting Force 0 bar: 40 N Connecting Force 6 bar: 120 N Vacuum Coupling: 96% Vacuum Plug: 96% Vacuum connected: 96%</p>
<p>Flow diagrams</p>		
<p>Air</p> 	<p>Air</p> 	
<p>Water</p> 	<p>Water</p> 	<p>Water</p> 





Couplings – with valve



Series 25KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	59,5	10,5	23	AISI 303	25KAAW13RVX
	G 1/4	19	59,5	10,5	23	AISI 316 L	25KAAW13EVX
	G 3/8	19	57,5	9	23	AISI 303	25KAAW17RVX
	G 3/8	19	57,5	9	23	AISI 316 L	25KAAW17EVX
	G 1/2	24	60,5	12	23	AISI 303	25KAAW21RVX
	G 1/2	24	60,5	12	23	AISI 316 L	25KAAW21EVX
 <p>Female Thread</p>	G 1/4	19	55,5	10	23	AISI 303	25KAIW13RVX
	G 1/4	19	55,5	10	23	AISI 316 L	25KAIW13EVX
	G 3/8	19	54,5	9	23	AISI 303	25KAIW17RVX
	G 3/8	19	54,5	9	23	AISI 316 L	25KAIW17EVX
	G 1/2	24	57,5	12	23	AISI 303	25KAIW21RVX
	G 1/2	24	57,5	12	23	AISI 316 L	25KAIW21EVX
 <p>Hose Barb</p>	6 mm	19	73,5	25	23	AISI 316 L	25KATF06EVX
	8 mm	19	73,5	25	23	AISI 316 L	25KATF08EVX
	9 mm	19	73,5	25	23	AISI 316 L	25KATF09EVX
	10 mm	19	73,5	25	23	AISI 303	25KATF10RVX
	13 mm	19	73,5	25	23	AISI 303	25KATF13RVX




Plugs – without valve




Series 25KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/8	14	31	7		AISI 303	25SFAW10RXX
	G 1/4	17	33	9		AISI 303	25SFAW13RXX
	G 1/4	17	33	9		AISI 316 L	25SFAW13EXX
	G 3/8	19	33	9		AISI 303	25SFAW17RXX
	G 3/8	19	33	9		AISI 316 L	25SFAW17EXX
	G 1/2	24	38	12		AISI 303	25SFAW21RXX
 <p>Female Thread</p>	G 1/2	24	38	12		AISI 316 L	25SFAW21EXX
	G 1/8	14	30	7		AISI 303	25SFIW10RXX
	G 1/4	17	33	10		AISI 303	25SFIW13RXX
	G 1/4	17	33	10		AISI 316 L	25SFIW13EXX
	G 3/8	19	33	10		AISI 303	25SFIW17RXX
	G 3/8	19	33	10		AISI 316 L	25SFIW17EXX
	G 1/2	24	35	12		AISI 303	25SFIW21RXX
	G 1/2	24	35	12		AISI 316 L	25SFIW21EXX




Plugs – without valve **Series 25KA**

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Hose Barb</p>	6 mm		48	25	12	AISI 303	25SFTF06RXX
	6 mm		48	25	12	AISI 316 L	25SFTF06EXX
	8 mm		48	25	12	AISI 303	25SFTF08RXX
	8 mm		48	25	12	AISI 316 L	25SFTF08EXX
	9 mm		48	25	12	AISI 303	25SFTF09RXX
	9 mm		48	25	12	AISI 316 L	25SFTF09EXX
	10 mm		48	25	12	AISI 303	25SFTF10RXX
	10 mm		48	25	12	AISI 316 L	25SFTF10EXX
	13 mm		48	25	15	AISI 303	25SFTF13RXX
	13 mm		48	25	15	AISI 316 L	25SFTF13EXX




Couplings – with valve **Series 25KB**

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	59,5	10,5	23	AISI 303	25KBAW13RVX
	G 1/4	19	59,5	10,5	23	AISI 316 L	25KBAW13EVX
	G 3/8	19	57,5	9	23	AISI 303	25KBAW17RVX
	G 3/8	19	57,5	9	23	AISI 316 L	25KBAW17EVX
	G 1/2	24	60,5	12	23	AISI 303	25KBAW21RVX
	G 1/2	24	60,5	12	23	AISI 316 L	25KBAW21EVX
 <p>Female Thread</p>	G 1/4	19	55,5	10	23	AISI 303	25KBIW13RVX
	G 1/4	19	55,5	10	23	AISI 316 L	25KBIW13EVX
	G 3/8	19	54,5	9	23	AISI 303	25KBIW17RVX
	G 3/8	19	54,5	9	23	AISI 316 L	25KBIW17EVX
	G 1/2	24	57,5	12	23	AISI 316 L	25KBIW21EVX
 <p>Hose Barb</p>	6 mm	19	73,5	25	23	AISI 316 L	25KBTF06EVX
	8 mm	19	73,5	25	23	AISI 316 L	25KBTF08EVX
	9 mm	19	73,5	25	23	AISI 316 L	25KBTF09EVX






	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	58	10,5		AISI 303	25SBAW13RVX
	G 1/4	19	58	10,5		AISI 316 L	25SBAW13EVX
	G 3/8	19	56	9		AISI 303	25SBAW17RVX
	G 3/8	19	56	9		AISI 316 L	25SBAW17EVX
	G 1/2	24	59	12		AISI 303	25SBAW21RVX
	G 1/2	24	59	12		AISI 316 L	25SBAW21EVX
 <p>Female Thread</p>	G 1/4	19	54	10		AISI 303	25SBIW13RVX
	G 1/4	19	54	10		AISI 316 L	25SBIW13EVX
	G 3/8	19	53	9		AISI 303	25SBIW17RVX
	G 3/8	19	53	9		AISI 316 L	25SBIW17EVX
	G 1/2	24	56	12		AISI 316 L	25SBIW21EVX
 <p>Hose Barb</p>	6 mm	19	72	25		AISI 316 L	25SBTF06EVX
	8 mm	19	72	25		AISI 316 L	25SBTF08EVX
	9 mm	19	72	25		AISI 316 L	25SBTF09EVX

Couplings – flat sealing Series 25KL


	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	59,5	10,5	23	AISI 303	25KLAW13RVX
	G 1/4	19	59,5	10,5	23	AISI 316 L	25KLAW13EVX
	G 3/8	19	57,5	9	23	AISI 303	25KLAW17RVX
	G 3/8	19	57,5	9	23	AISI 316 L	25KLAW17EVX
	G 1/2	24	60,5	12	23	AISI 303	25KLAW21RVX
	G 1/2	24	60,5	12	23	AISI 316 L	25KLAW21EVX
 <p>Female Thread</p>	G 1/4	19	55,5	10	23	AISI 303	25KLIW13RVX
	G 1/4	19	55,5	10	23	AISI 316 L	25KLIW13EVX
	G 3/8	19	54,5	9	23	AISI 303	25KLIW17RVX
	G 3/8	19	54,5	9	23	AISI 316 L	25KLIW17EVX
	G 1/2	24	57,5	12	23	AISI 303	25KLIW21RVX
	G 1/2	24	57,5	12	23	AISI 316 L	25KLIW21EVX
 <p>Hose Barb</p>	9 mm	19	73,5	25	23	AISI 303	25KLTf09RVX
	9 mm	19	73,5	25	23	AISI 316 L	25KLTf09EVX

Plugs – flat sealing Series 25KL

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	19	58	10,5		AISI 303	25SLAW13RVX
	G 1/4	19	58	10,5		AISI 316 L	25SLAW13EVX
	G 3/8	19	56	9		AISI 303	25SLAW17RVX
	G 3/8	19	56	9		AISI 316 L	25SLAW17EVX
	G 1/2	24	59	12		AISI 303	25SLAW21RVX
	G 1/2	24	59	12		AISI 316 L	25SLAW21EVX
 <p>Female Thread</p>	G 1/4	19	54	10		AISI 303	25SLIW13RVX
	G 1/4	19	54	10		AISI 316 L	25SLIW13EVX
	G 3/8	19	53	9		AISI 303	25SLIW17RVX
	G 3/8	19	53	9		AISI 316 L	25SLIW17EVX
	G 1/2	24	56	12		AISI 303	25SLIW21RVX
	G 1/2	24	56	12		AISI 316 L	25SLIW21EVX
 <p>Hose Barb</p>	6 mm	19	75	25		AISI 303	25SLTF06RVX
	9 mm	19	72	25		AISI 303	25SLTF09RVX
	9 mm	19	72	25		AISI 316 L	25SLTF09EVX

Nominal Diameter

10 = 80 mm²



Rectus Series

27

Low Pressure



1/2" universal industrial coupling with standard European profile for use with large pneumatic consumers. Coupling system with single-hand operation. High Flow valve for optimum flow and low pressure drop. The series stands out for its robust design, extremely high flow and long service life even with the harshest use. The collar design minimises damage to the valve body.

Dust Protections  (P. 250)
for Coupling Part.-No. SK27S

Working Temperature*
-15°C up to +200°C (FKM)
depending on the medium.

* For temperatures below -15°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.

Series 27 with additional end connections available on request.

Other designs in series 27

The following other designs can be found from page:

- ▶ Brass / Steel P: 86
- ▶ Safety Self-Venting P: 232

Interchangeability (KA only)

- Cejn 410



Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

35 bar

Material

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Coupling: AISI 303 / AISI 316 L
Plug: AISI 303 / AISI 316 L
Seals: FKM

Technical Description

Connecting Force 0 bar: 60 N
Connecting Force 6 bar: 180 N





Dead space volume: 2,2 ml

Vacuum Coupling: 87%
Available on request with O-ring seal for vacuum when coupled.

Connecting Force 0 bar: 60 N
Connecting Force 6 bar: 180 N

Vacuum Coupling: 96%
Vacuum Plug: 96%
Available on request with O-ring seal for vacuum when coupled.




Flow diagrams





Couplings – with valve




Series 27KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 3/8	24	57,5	9	27	AISI 303	27KAAW17RVX
	G 3/8	24	57,5	9	27	AISI 316 L	27KAAW17EVX
	G 1/2	24	59,5	12	27	AISI 303	27KAAW21RVX
	G 1/2	24	59,5	12	27	AISI 316 L	27KAAW21EVX
	G 3/4	32	60,5	16	27	AISI 303	27KAAW26RVX
	G 3/4	32	60,5	16	27	AISI 316 L	27KAAW26EVX
 <p>Female Thread</p>	G 1/2	24	56,5	12	27	AISI 303	27KAIW21RVX
	G 1/2	24	56,5	12	27	AISI 316 L	27KAIW21EVX
	G 3/4	32	60,5	16	27	AISI 316 L	27KAIW26EVX
 <p>Hose Barb</p>	13 mm	24	76,5	25	27	AISI 303	27KATF13RVX
	13 mm	24	76,5	25	27	AISI 316 L	27KATF13EVX






Plugs – without valve




Series 27KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/4	17	36,5	9		AISI 303	27SFAW13RXX
	G 1/4	17	36,5	9		AISI 316 L	27SFAW13EXX
	G 3/8	19	36,5	9		AISI 303	27SFAW17RXX
	G 1/2	24	40	12		AISI 303	27SFAW21RXX
	G 1/2	24	40	12		AISI 316 L	27SFAW21EXX
 <p>Female Thread</p>	G 1/2	24	37	12		AISI 303	27SFIW21RXX
	G 1/2	24	37	12		AISI 316 L	27SFIW21EXX
	G 3/4	32	42	16		AISI 303	27SFIW26RXX
 <p>Hose Barb</p>	8 mm		48	25	15	AISI 303	27SFTF08RXX
	9 mm		48	25	15	AISI 303	27SFTF09RXX
	13 mm		48	25	15	AISI 303	27SFTF13RXX
	13 mm		48	25	15	AISI 316 L	27SFTF13EXX
	19 mm		49	25	21	AISI 303	27SFTF19RXX

Couplings – with valve **Series 27KB**


	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 3/8	24	57,5	9	27	AISI 303	27KBAW17RVX
	G 3/8	24	57,5	9	27	AISI 316 L	27KBAW17EVX
	G 1/2	24	59,5	12	27	AISI 303	27KBAW21RVX
	G 1/2	24	59,5	12	27	AISI 316 L	27KBAW21EVX
	G 3/4	32	60,5	16	27	AISI 316 L	27KBAW26EVX
 <p>Female Thread</p>	G 1/2	24	56,5	12	27	AISI 303	27KBIW21RVX
	G 1/2	24	56,5	12	27	AISI 316 L	27KBIW21EVX
 <p>Hose Barb</p>	13 mm	24	76,5	25	27	AISI 316 L	27KBTF13EVX

Plugs – with valve **Series 27KB**

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	24	57,5	12		AISI 303	27SBAW21RVX
	G 1/2	24	57,5	12		AISI 316 L	27SBAW21EVX
 <p>Female Thread</p>	G 1/4	24	54,5	10		AISI 316 L	27SBIW13EVX
	G 1/2	24	54,5	12		AISI 303	27SBIW21RVX
	G 1/2	24	54,5	12		AISI 316 L	27SBIW21EVX
 <p>Hose Barb</p>	13 mm	24	74,5	25		AISI 303	27SBTF13RVX
	13 mm	24	74,5	25		AISI 316 L	27SBTF13EVX

Nominal Diameter

9,5 = 71 mm²



Tema Series

1800

Low Pressure



Other designs in series 1800

The following other designs can be found from page:

► Brass / Steel P. 94

The 1800 series in stainless steel is used mainly for applications in the area of liquids with aggressive media. The coupling system stands out for its robust, compact design and high corrosion resistance. Ultra High Flow valve for optimum flow and low pressure drop.

Series 1800 with additional end connections available on request.

Dust Protections  (P. 250) for Coupling Part.-No. 5026-QC for Plug Part.-No. 2526-QC

Working Temperature*
-25°C up to +200°C (FKM) depending on the medium.

* For temperatures below -25°C and over +200°C and depending on the medium, other seal variants (EPDM, FFKM) are available.



Working Pressure**

35 bar
** maximum static working pressure with design factor 4 to 1.

50 bar

Features

- Single-hand operation
- Two-hand operation

Material




Coupling: AISI 303 / AISI 316
Plug: AISI 303 / AISI 316
Seals: FKM

Coupling: AISI 316
Plug: AISI 316
Seals: FKM

Interchangeability (KA only)

- Tema Design

Flow diagrams





WE MAKE YOUR TECHNOLOGY WORK



Couplings – with valve




Series 1800KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	22	54	13	27	AISI 316	1800KAAW21EVX
 <p>Female Thread</p>	G 3/8	22	54	10	27	AISI 316	1800KAIW17EVX
	G 1/2	24	55	10	27	AISI 316	1800KAIW21EVX





Plugs – without valve


Series 1800KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 3/8	19	36	10		AISI 316	1800SFAW17EXX
 <p>Female Thread</p>	G 3/8	22	36	10		AISI 316	1800SFIW17EXX
 <p>Hose Barb</p>	6 mm		44	23	16	AISI 303	1800SFTF06RXX





Couplings – with valve **Series 1800KB**

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Male Thread</p>	G 1/2	22	54	10	27	AISI 316	1800KBAW21EVX
 <p>Female Thread</p>	G 3/8	22	54	9	27	AISI 316	1800KBIW17EVX
	G 1/2	24	55	9	27	AISI 316	1800KBIW21EVX

Plugs – with valve **Series 1800KB**

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 <p>Female Thread</p>	G 3/8	22	49	10		AISI 316	1800SBIW17EVX
	G 1/2	25	50	9		AISI 316	1800SBIW21EVX

Cross-Reference-List

Connection	Thread	Rectus Part Number old	Tema Part Number old	Part Number new	Page
 Couplings – with valve					
Male Thread	G 1/2		1800 ARV	1800KAAW21EVX	161
Female Thread	G 3/8		1800 RV	1800KAIW17EVX	161
	G 1/2		1800 BRV	1800KAIW21EVX	161
 Plugs – without valve					
Male Thread	G 3/8		18210 R	1800SFAW17EXX	161
Female Thread	G 3/8		18410 R	1800SFIW17EXX	161
Hose Barb	6 mm		18006 RF	1800SFTF06RXX	161
 Couplings – with valve					
Male Thread	G 1/2		1800 NARV	1800KBAW21EVX	162
Female Thread	G 3/8		1800 NRV	1800KBIW17EVX	162
	G 1/2		1800 NBRV	1800KBIW21EVX	162
 Plugs – with valve					
Female Thread	G 3/8		18410 RV	1800SBIW17EVX	162
	G 1/2		18422 RV	1800SBIW21EVX	162